

WHISKY TIRE & RIM COMPATIBILITY CHART



RIM	MAXIMUM TIRE SIZE*	MINIMUM TIRE SIZE	ETRTO	TUBELESS READY**	ASTM CONDITION***
No.9 30D Road	700c x 40mm	700c x 25mm	622 x 19c	Yes	2
No.9 50D Road/CX	700c x 40mm	700c x 25mm	622 x 19c	Yes	2
No.9 30W Mountain 29"	29 x 2.5"	29 x 1.5"	622 x 24c	Yes	3
No.9 30W Mountain 27.5"	27.5 x 2.5"	27.5 x 1.5"	584 x 24c	Yes	3
No.9 36W Mountain 29"	29 x 2.6"	29 x 2.25"	622 x 30c	Yes	3
No.9 36W Mountain 27.5"	27.5 x 2.6"	27.5 x 2.25"	584 x 30c	Yes	3
No.9 40W Plus 29"	29 x 3"	29 x 2.35"	622 x 36c	Yes	3
No.9 40W Plus 27.5"	27.5 x 3"	27.5 x 2.35"	584 x 36c	Yes	3
No.9 41W Carbon Trail 29"	29 x 3.0"	29 x 2.1"	622 x 36c	Yes	3
No.9 41W Carbon Trail 27.5"	27.5 x 3.0"	27.5 x 2.1"	584 x 36c	Yes	3
No.9 29W Carbon Goat	29 x 2.35"	700c x 32mm	622 x 23c	Yes	3
No.9 50W Carbon 27.5+	27.5 x 3.5"	27.5 x 2.8"	584 x 44.5c	Yes	3
No.9 70W Carbon Fat	26 x 4.8"	26 x 3.8"	559 x 65c	Yes	3
No.9 80W Carbon Fat	27.5 x 4.8"	27.5 x 3.8"	584 x 77c	Yes	3
No.9 100W Wide Carbon Fat	26 x 5.05"	26 x 3.8"	559 x 94.5c	Yes	3

* Max tire refers to the maximum recommended tire size for use with this rim. Follow manufacturers recommendations for clearance on bicycles and accessories in use.

** For tubeless use, Whisky rims must be used with tubeless ready tires, tubeless rim tape, and tubeless sealant. Please refer to whiskyparts.co/safety for complete tubeless instructions.

*** ASTM Condition definitions can be found at whiskyparts.com/safety.